Page 1 of 9

006366323 [file://C:\WINDOWS\TEMP\006366323 cpc]

EP

(12) United States Patent Shono US006366323B1
(10) Patent No.: US 6,366,323 B1

(45) Date of Patent:

Apr. 2, 2002

(54)	DIGITAL CAMERA WITH MOVEABLE IMAGE PICKUP DEVICE				
(75)	inventor:	Tetsriji Shono, Saitama-kon (IP)			
(73)	Assignee:	Asuhi Kogoku Kogyo Kabushiki Kalshu, Tokyo (JP)			
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days			
(21) Appl No: 09/089,404					
(22)	Filed:	Jun. 3, 1998			
(30) Foreign Application Priority Data					
Jun	12, 1997	(开) 9-155144			
(51)	Int. Cl.?	G03B 17/00; G03B 7/99; G03B 17/04			
(52)	U.S. Cl. ;	348/340; 348/335; 348/373; 348/374; 396/75; 396/270; 396/349			
(58)	Field of S	enreh			
(56)		References Ched			
US PATENT DOCUMENTS					
	4,803,557 A 4,961,115 A 5,557,327 A 5,706,051 A 5,031,998 A	* 10/1990 Jessop			

FOREIGN PATENT DOCUMENTS
000549300 A1 • 6/1993

 8/1994 10/1994 1/1996 		G02B/7/04 - H04N/5/232 H04N/5/232
1/1770		DO414/3/232
7/1996		H04N/5/232
9/1996	·	HO4N/5/232
	7/1996	-, -, -

cited by examiner

Primary Examiner—Wendy R Garber Assistant Examiner—John M Villecco (74) Attorney, Agent, or Firm—Greenblum & Bernstein, P.L. C

(57) ABSTRACT

A digital camera which includes: a photographic lens movable along an optical axis thereof between a retracted position and a photographing position in front of the retracted position; an image pickt-up device on which an object image is formed through the photographic lens, the image pick-up device being guided to be movable between a first position where the image pick-up device is positioned in a photographic lens path of the photographic lens behind the photographic lens and a second position where the image pick-up device is positioned out of the photographic optical path; and a mechanism for moving the image pick-up device between the first position and the second position, wherein the moving mechanism moves the image pick-up device to the first position to the photographic lens is moved from the retracted position to the photographing position, and wherein the moving mechanism moves the image pick-up device to the second position when the photographic lens is moved from the photographing position to the retracted position

13 Claims, 3 Drawing Sheets

